

DATASHEET

The small Ambu BlueSensor P features conductive wet gel, offset connector and suitable adhesion to ensure stable signal quality during short term applications. It can be used on children. Thanks to the adhesive, the electrode is gentle to the skin.

Key benefits

- Offset connector mitigates the impact on signal quality from external forces like pulling of lead wires and pressure on electrodes
- Offset connector allows the user to connect and disconnect the lead wire without applying pressure to the patient or the sensor area, which reduces the risk of gel spreading and adhesive detachment from skin
- Conductive wet gel lowers skin impedance effectively and immediately
- Wet gel optimizes contact between skin and electrode
- Adhesive is gentle to the skin and suitable for short-term application
- Ag/AgCl sensor ensures stable signal quality

Ambu® BlueSensor P

ECG Electrode

Single use



Wet gel



Foam backing



Silver sensor

BlueSensor

Ambu

SPECIFICATIONS

Dimensions

Electrode size (length x width in mm)	40 x 34
Skin contact size (diameter in mm)	34
Adhesive area (in mm ²)	754

Sensor

Sensor material	Silver/silver chloride (Ag/AgCl)
Gel system	Wet gel
Gel area (in mm ²)	154

Electrical data (ANSI/AAMI)

AC impedance - typical	650 Ω
DC offset voltage - typical	3.1 mV
Defibrillation overload recovery - typical	11.35 mV
Rate of change of polarization potential - typical	-0.18 mV/s
Combined offset instability and internal noise	8.2 μV
Bias current tolerance (over 8 hours)	6.4 mV

MATERIALS

Electrode

Bio-compatible	Yes
Sponge	Polyurethane foam (PUR)
Backing material	Polyvinyl chloride foam (PVC)
Skin adhesive	Acrylate
Upper part	Polyvinyl chloride film (PVC)
Fitting	Polypropylene (PP)
Connector (stud)	Stainless steel
Eyelet	Silver coated plastic
Release liner	Polyethylene film (PE)/Amorphous Polyethylene Terephthalate (APET)

AVAILABLE CONFIGURATIONS*

Reference number	Units/liner	Units/pouch	Units/inner box	Units/outer box
P-00-S/10	1	10	1000	2000
P-00-S/12	1	12	960	1920
P-00-A/50	1	50	1000	2000
P-00-F/50	1	50	1000	2000
P-00-S/50	1	50	1000	2000

P-00-S ■ Product ■ Wire length ■ Connector

*some configurations may not be available worldwide

Environment

Electrode is not made with natural rubber latex

Packaging is PVC-free

X-ray & MRI

Radiolucent	No
MR Conditional	No

Shelf life

Opened pouches	1 month
Unopened pouch*	15 months

*from date of production

Packaging

Pouch (outer/middle/inner layers)	Polyester/ Aluminium/ Polyethylene
Boxes	Cardboard

Options

Non-wired connectors S, A, F

Precaution

Single use only

CONNECTORS



S = Stud



A = 4 mm fitting



F = 3 mm fitting

FEATURES



Printed release liner

Ambu

■ Ambu A/S

Baltorpbakken 13
2750 Ballerup
Denmark
T +45 72 25 20 00
ambu.com

CE US: Rx only