





Name	Premium 10 0 Hg
Cell Chemistry	Zinc Air
Designation	IEC: PR70, ANSI: 7005ZD, Common: 10
Nominal Voltage	1.45 volts
Weight	0.31 grams (0.011 oz)
Volume	0.08 cc (0.005 cu. in.)
Operating Temperature Range	-10°C to 50°C (14°F to 122°F)
Impedance	< 9.0 ohm @ AC 1000 Hz
ANSI Standard	94 hours - 1 mA background, 5 mA 100 ms pulse once every 2 hr, 12 hr/day to 1.05V at 21°C (70°F) and 50% RH
IEC Standard	55 hours - 1.5 mA background, 5 mA 100 ms pulse once every 2 hr, 12 hr/day to 1.1V at 21°C (70°F) and 50% RH
IEC/ANSI Wireless Streaming	38 hours - 1.5 mA background 45 min, 3 mA 15 min pulse once every hour, 12 hr/day to 1.1V at 21°C (70°F) and 50% RH
How to Use	Hearing Aid Instruments: Remove and discard the plastic tab covering air holes. Allow the battery to stand for fifteen seconds to ensure proper activation.
Storage Conditions	Batteries should be stored in ambient conditions between +10°C (50°F) and +30°C (86°F). Avoid direct sunlight.
Shelf Life	Four years with tab applied when stored at 21°C (70°F)
Environmental	These cells have no added mercury. Refer to Rayovac Safety Data Sheets for more detailed information.
Compliant to the following Standards	IEC 60086-1, IEC 60086-2, ANSI C18.1M Parts 1 & 2



DIMENSIONS SHOWN ARE IEC STANDARDS FOR ENGINEERING TOLERANCES CONTACT RAYOVAC.

Typical IEC Standard Discharge Performance



Important Notice

Do not duplicate or distribute without written permission from Energizer Holdings, Inc. This data sheet contains typical performance information specific to products manufactured at the time of its publication. This data is subject to change without prior notice. Contact your account manager for latest information.

Rayovac a division of Energizer Holdings: www.rayovac.com | www.rayovac.eu
Contents herein do not constitute a warranty and are for reference only.